













Tableau des caractéristiques techniques: Fauteuils Roulants Manuels

		Assise					
		Largeur (mm) 	Profondeur (mm) 	Pente 	Hauteur sol/siège (mm) 	UL (mm) 	
FAUTEUILS MEDIUM ACTIFS							
 Action^{NG}	Standard	380 [...] 480	400 / 450 / 500	0° / 3° / 6°	360 [...] 510	200 à 400/330 à 460/440 à 510	
	Transit				460 [...] 510		
	Dual HR			400 / 450	0°		460 / 485
	Levier Pendulaire		0° / 3° / 6°		460 [...] 510		
	XLT			505 / 555 / 605	400 / 450 / 500		0° / 3° / 6°
	Matrx		380 [...] 480	400 / 450			
 Action^{NG}	Standard	380 [...] 505	400/450	0° / 3° / 6°	360 à 510	200 à 400/330 à 460/440 à 510	
	Transit				460 [...] 510		
	Dual HR				435 [...] 485		
	Levier Pendulaire				460 [...] 510		
	Confort				405 [...] 505		360 [...] 460
	Matrx				380 [...] 505		360 à 510
 Action^{NG}		405 / 430 / 455 / 480	400 à 425	3°	460 / 485	330 à 460	
 Action^{NG}	Standard	405 [...] 505	425	3°	450/500	330 à 455	
	Transit						
	Dual HR						
 Alu Lite		410 / 460	430	3°	490	-	
 Topaz		660 / 710 / 760	460 / 510	3°	445 / 495	-	
FAUTEUILS ENFANTS							
 Action^{Junior}	Standard	305 / 330 / 355	305 / 350	1,5° / 5° / 8,5°	410 / 435 / 460	130 à 260 / 220 à 320 / 300 à 450	
	Evolutif	205 à 280 / 305 à 380	200 [...] 350 / 275 [...] 375				